



Cashless ATM 8319



CASHLESS 8319 5th Generation

Cashless ATM is an intelligent, Low cost, easily manageable and maintainable new generation of banking devices. This product offers high performance and cost efficient options for account inquiries and online transactions, bill payment, IC card recharging and other self-service businesses cashless ATM is the best solution to extend bank outlets and increase bank competitive advantages.

Features:

- Windows based
- LTE / LAN module
- High resolution camera
- Dual Amplified speaker
- 19" Touch screen + Privacy Filter
- Metal pin pad/PCI certified
- Magnetic card reader
- IC card reader/writer
- RFID card reader/writer
- Microphone
- Low power consumption and fan less design
- User friendly interface
- Easy to set up and able to work in the extremely tough indoor and out-door environment
- Low maintenance cost
- Fingerprint Scanner Identification
- WOSA / XFS Support



15th floor, Al Masraf Tower
1505-39, Dubai, UAE
P.O Box: 13774
Tel: +971 4 29 56 561
Fax: +971 4 29 56 593
www.gssint.com
register@gssint.com



Specifications:

IPC	CPU Intel Core i5 7th, 9th and 11th Generation, RAM 4/8GB, HDD 500GB - SSD 128/256/500GB Integrated sound card, graphic card, net card interfaces: USBx12, RS232x6, HDMIx1, VGAX1, RJ45x2, Wifi module, Bluetooth Module and LTE included.
Touch Monitor	19 inch touch + privacy filter Touch type: Capacitive multi touch
Magnetic Reader	1-standard:ISO 7811 2-card read speed:3 ~ 60 inch/s 3-Interface:USB2.0 4-read card: 1, 2, 3 track
IC Smart Card Reader	ISO/IEC 7816, EMV Certified
Fingerprint Scanner	Optical – PIV Certified
Receipt Printer	Thermal Printing Method Printing Speed:100 mm/s Paper Width: 60 mm Auto Cut Near-end Sensor Use better material With metal door
EPP	PCI Certified The algorithm supports: DES, Triple DES, RSA, SM2, SM3, SM4; Key press life: 2 millions; Key press force: 2 ~ 4 N; Key press travel: not less than 0.4mm; Interface: RS232 or USB
QR scanner	Optical system:CMOS Highly sensitive sensor Capture light source:Hidden white LED Sensitivity: tilt $\pm 30^\circ$ deflect $\pm 40^\circ$ rotate 360° Contrast: 20% Resolution:640x480 Code System 1D:Code 128,EAN-13,EAN-8, Code 39,UPC-A,UPC-E,Codabar,Interleaved 2 of 5,ITF-6,ITF-14,ISBN,Code 93,UCC/ EAN-128,GS1 Databar,Matrix 2 of 5,Code11, Industrial 2 of 5,Standard 2 of 5,MSI Code System 2D: QR Code Reading accuracy: More than 5mil Field of view:60° Ability to scan from a display like mobile phones
Power Supply	12V10A DC power supply
Camera	Resolution:2592*1944 , USB interface (5MP)
Supervisor Key	Controlled by the indicating light controller Door Sensor
Top Lightbox	Kiosk top lighting, single color
Speakers	High Quality
Cabinet	Made by CR steel, wall mounted
Package	Carton box

* All the marked items can be changed upon customer request.